

Features

Discrete elegant lines, minimal physical intrusion from ceiling when installed.

Installation and maintenance made simple through use of the integral ceiling bracketry.

Made from durable materials including a metal enclosure for fire safety.

Applications

Distributed audio/public address system component, for commercial and retail sector areas.

Widely used in a variety of areas such as: hotels, shopping malls, schools, religious establishments, hospitals and conferencing.



CL Series Ceiling Speakers

OHM believe that the sound in a venue should be uncompromised, including the often overlooked secondary areas. To this end we are proud to introduce ceiling speakers within our range of systems so that the performance and aesthetic design expected of OHM products can be consistent throughout the venue.

Additional models have been introduced for applications that require metal fire domes to comply with fire regulations. The plastic parts are moulded in fire retardant graded materials.

CL-2TD

The CL-TD range of full range ceiling speakers are all enclosed in a metal domed casing to comply with the fire regulations in countries. Using the same quick mount system as the rest of the CL family, the CL-2TD has a built in crossover and will handle 60 watts RMS.

Contents

- 1 x CL-2TD loudspeaker
- 1 x Instruction Sheet
- 1 x Mounting cutout template

Thank you for purchasing the OHM CL-2TD, please take the time to check all items are present and undamaged. If there is damage to the carton on delivery please ensure this is written on the delivery note and if a claim is required contact the delivery company as soon as possible. Only the consignee can file a claim against the carrier for shipping damage. Be sure to save the carton and all packing materials for the carriers inspection.

Please take the time to fill in the guarantee card included with this ceiling speaker and return it to OHM retaining the customer portion for your records. Non compliance will not affect your statutory rights but may affect any claim in respect of time bound failures.

Please note specifications may be subject to change without notice. E & O.E

Technical Specification	
Design	Full Range
Woofer	6 inch
Impedance	8Ω / 100V
Power Handling RMS	30 Watts
Programme Watts	60 Watts
SPL 1W/1m (dB)	88 dB
Max @1m (dB)	105 dB
Frequency Response	90Hz-20kHz
Dispersion	140° Conical
Crossover Frequency	3kHz

Product Features						
Ceiling Thickness	10 - 35 mm					
Hole Cutout Ø	Ø200 mm					
Dimensions Ø x H	Ø230 x 150 mm					
Weight	2.2 kg					
Connector	Spring loaded terminal					
Tappings	100V	-	30W	15W	7.5W	3.8W
	70V	30W	15W	7.5W	3.8W	1.9W
	IMP (Ω)	163	333	667	1.3k	2.6k
Colour	White Ral9003					
Speaker Cables	Minimum Diameter 2.5mm ²					

Installation Instructions

The installation of this OHM product couldn't be easier:

1. Ensure there is enough clear space to house the speaker.
2. Take the template provided, position on the ceiling at the point where the speaker will be fitted, draw around the circle and cut a hole in the ceiling to fit.
3. Remove the grill from the speaker by gently pushing the mounting poles down until they ease the grill out, position the rear of the speaker facing into the hole. (fig. 1)
4. Connect speaker to amplification/system ensuring all connections are correct. (fig. 2)
5. Turn the plastic fixing points until the ends are located over the ceiling, tighten the screw until the speaker is clamped on to the ceiling. (fig. 3)
6. Replace the speaker grill. (fig. 4)
7. Turn on music source and enjoy the amazing sound of the OHM loudspeaker.

Mounting Instructions

